

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Ethylenediamine

Product Number : E1521
Brand : Sigma

Supplier : Sigma-Aldrich
3050 Spruce Street
SAINT LOUIS MO 63103
USA

Telephone : +1 800-325-5832
Fax : +1 800-325-5052
Emergency Phone # (For both supplier and manufacturer) : (314) 776-6555

Preparation Information : Sigma-Aldrich Corporation
Product Safety - Americas Region
1-800-521-8956

2. HAZARDS IDENTIFICATION

Emergency Overview

OSHA Hazards

Combustible Liquid, Target Organ Effect, Harmful by ingestion., Skin and respiratory sensitizer, Corrosive

Target Organs

Kidney, Liver, Blood, Lungs

Other hazards which do not result in classification

Lachrymator., Rapidly absorbed through skin.

GHS Classification

Flammable liquids (Category 3)
Acute toxicity, Oral (Category 4)
Acute toxicity, Dermal (Category 4)
Skin irritation (Category 2)
Serious eye damage (Category 1)
Respiratory sensitization (Category 1)
Skin sensitization (Category 1)
Acute aquatic toxicity (Category 2)

GHS Label elements, including precautionary statements

Pictogram



Signal word

Danger

Hazard statement(s)

H226 Flammable liquid and vapour.
H302 + H312 Harmful if swallowed or in contact with skin
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H401 Toxic to aquatic life.

Precautionary statement(s)

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P280 Wear protective gloves/ eye protection/ face protection.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/ physician.

HMIS Classification

Health hazard: 3
Chronic Health Hazard: *
Flammability: 2
Physical hazards: 0

NFPA Rating

Health hazard: 3
Fire: 2
Reactivity Hazard: 0

Potential Health Effects

Inhalation May be harmful if inhaled. Material is extremely destructive to the tissue of the mucous membranes and upper respiratory tract.
Skin Harmful if absorbed through skin. Causes skin burns.
Eyes Causes eye burns.
Ingestion Harmful if swallowed.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms : 1,2-Diaminoethane
Formula : C₂H₈N₂
Molecular Weight : 60.10 g/mol

Component	Concentration
Ethylenediamine	
CAS-No. 107-15-3	-
EC-No. 203-468-6	
Index-No. 612-006-00-6	

4. FIRST AID MEASURES

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. Continue rinsing eyes during transport to hospital.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

5. FIREFIGHTING MEASURES

Conditions of flammability

Flammable in the presence of a source of ignition when the temperature is above the flash point. Keep away from heat/sparks/open flame/hot surface. No smoking.

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Specific hazards arising from the chemical

Flash back possible over considerable distance. Container explosion may occur under fire conditions. Vapours may form explosive mixture with air.

Special protective equipment for firefighters

Wear self contained breathing apparatus for fire fighting if necessary.

Hazardous combustion products

Hazardous decomposition products formed under fire conditions. - Carbon oxides, nitrogen oxides (NOx)

Further information

Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions**

Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

7. HANDLING AND STORAGE**Precautions for safe handling**

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

Conditions for safe storage

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Air and moisture sensitive. Handle and store under inert gas.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Components	CAS-No.	Value	Control parameters	Basis
Ethylenediamine	107-15-3	TWA	10 ppm	USA. ACGIH Threshold Limit Values (TLV)
Remarks	Not classifiable as a human carcinogen Danger of cutaneous absorption			
		TWA	10 ppm 25 mg/m ³	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
		TWA	10 ppm 25 mg/m ³	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
	The value in mg/m ³ is approximate.			
		TWA	10 ppm 25 mg/m ³	USA. NIOSH Recommended Exposure Limits

Personal protective equipment

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Hand protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Immersion protection

Material: butyl-rubber

Minimum layer thickness: 0.3 mm

Break through time: > 480 min

Material tested: Butoject® (Aldrich Z677647, Size M)

Splash protection

Material: Nature latex/chloroprene

Minimum layer thickness: 0.6 mm

Break through time: > 30 min

Material tested: Lapren® (Aldrich Z677558, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 873000, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an Industrial Hygienist familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Eye protection

Tightly fitting safety goggles. Faceshield (8-inch minimum). Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin and body protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Form	liquid
Colour	no data available

Safety data

pH	12.2 at 110 g/l at 20 °C (68 °F)
Melting point/freezing point	Melting point/range: 8.5 °C (47.3 °F)
Boiling point	118 °C (244 °F)
Flash point	38 °C (100 °F) - closed cup
Ignition temperature	379 °C (714 °F)
Autoignition temperature	no data available
Lower explosion limit	2.7 %(V)

Upper explosion limit	16 %(V)
Vapour pressure	13 hPa (10 mmHg) at 20 °C (68 °F)
Density	0.899 g/mL at 25 °C (77 °F)
Water solubility	soluble
Partition coefficient: n-octanol/water	log Pow: -2.04
Relative vapour density	2.07 - (Air = 1.0)
Odour	no data available
Odour Threshold	no data available
Evaporation rate	no data available

10. STABILITY AND REACTIVITY

Chemical stability

Absorbs carbon dioxide (CO₂) from air. Stable under recommended storage conditions.

Possibility of hazardous reactions

no data available

Conditions to avoid

Air Exposure to moisture.
Heat, flames and sparks.

Materials to avoid

Oxidizing agents, Phosphorus halides, Aldehydes, Organic halides

Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides, nitrogen oxides (NO_x)
Other decomposition products - no data available

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Oral LD50

LD50 Oral - rat - 1,200 mg/kg
Remarks: Behavioral:Ataxia.

Inhalation LC50

LC50 Inhalation - mouse - 300 mg/m³

Dermal LD50

no data available

Other information on acute toxicity

no data available

Skin corrosion/irritation

Skin - rabbit - Severe skin irritation

Serious eye damage/eye irritation

Eyes - rabbit - Severe eye irritation

Respiratory or skin sensitization

May cause allergic respiratory and skin reactions

Germ cell mutagenicity

no data available

Carcinogenicity

Carcinogenicity - This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

- IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
- NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

no data available

Teratogenicity

no data available

Specific target organ toxicity - single exposure (Globally Harmonized System)

no data available

Specific target organ toxicity - repeated exposure (Globally Harmonized System)

no data available

Aspiration hazard

no data available

Potential health effects

- | | |
|-------------------|---|
| Inhalation | May be harmful if inhaled. Material is extremely destructive to the tissue of the mucous membranes and upper respiratory tract. |
| Ingestion | Harmful if swallowed. |
| Skin | Harmful if absorbed through skin. Causes skin burns. |
| Eyes | Causes eye burns. |

Signs and Symptoms of Exposure

Vomiting, Diarrhoea, Abdominal pain

Synergistic effects

no data available

Additional Information

RTECS: KH8575000

12. ECOLOGICAL INFORMATION

Toxicity

- | | |
|---|--|
| Toxicity to fish | LC50 - Pimephales promelas (fathead minnow) - 115.7 mg/l - 96 h |
| Toxicity to daphnia and other aquatic invertebrates | EC50 - Daphnia magna (Water flea) - 3 mg/l - 48 h |
| Toxicity to algae | EC50 - Pseudokirchneriella subcapitata (green algae) - 151 mg/l - 96 h |

Persistence and degradability

- | | |
|------------------|---|
| Biodegradability | Biotic/Aerobic
Result: 94 % - Readily biodegradable. |
|------------------|---|

Bioaccumulative potential

no data available

Mobility in soil

no data available

PBT and vPvB assessment

no data available

Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Toxic to aquatic life.

Avoid release to the environment.

13. DISPOSAL CONSIDERATIONS

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

UN number: 1604 Class: 8 (3) Packing group: II

Proper shipping name: Ethylenediamine

Reportable Quantity (RQ): 5000 lbs

Marine pollutant: No

Poison Inhalation Hazard: No

IMDG

UN number: 1604 Class: 8 (3) Packing group: II EMS-No: F-E, S-C

Proper shipping name: ETHYLENEDIAMINE

Marine pollutant: No

IATA

UN number: 1604 Class: 8 (3) Packing group: II

Proper shipping name: Ethylenediamine

15. REGULATORY INFORMATION

OSHA Hazards

Combustible Liquid, Target Organ Effect, Harmful by ingestion., Skin and respiratory sensitizer, Corrosive

SARA 302 Components

The following components are subject to reporting levels established by SARA Title III, Section 302:

	CAS-No.	Revision Date
Ethylenediamine	107-15-3	2007-03-01

SARA 313 Components

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

	CAS-No.	Revision Date
Ethylenediamine	107-15-3	2007-03-01

Pennsylvania Right To Know Components

	CAS-No.	Revision Date
Ethylenediamine	107-15-3	2007-03-01

New Jersey Right To Know Components

	CAS-No.	Revision Date
Ethylenediamine	107-15-3	2007-03-01

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

16. OTHER INFORMATION**Further information**

Copyright 2012 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.
